

2W(UD)系列电磁阀


2W (UD) Series Solenoid Valve



订购码 | Ordering Code

2W	025	-	06	NO	AC110V	E
规格代码 2W: 二位二通电磁阀(直动式) 2WH: 二位二通电磁阀(高压直动式) 2S: 不锈钢二位二通电磁阀(直动式) 2SH: 不锈钢二位二通电磁阀(高压直动式) Specification Code 2W: Two position two way solenoid valve(direct drive type) 2WH: Two position two way solenoid valve(high pressure direct drive type) 2S: Stainless steel two position two way solenoid valve(direct drive type) 2SH: Stainless steel two position two way solenoid valve(high pressure direct drive type)	流量孔径 Aperture of Flow Rate 012: 1.2mm 020: 2.0mm 025: 2.5mm 040: 4.0mm		接管口径 Joint Pipe Bore 06: 1/8" 08: 1/4" 10: 3/8"	初始状态 空白: 常闭型 NO: 常开型 Initial Estate Blank: Normal Close NO: Normal Open	标准电压 Standard Voltage DC12V DC24V AC24V 50/60Hz AC36V 50/60Hz AC110V 50/60Hz AC220V 50/60Hz AC380V 50/60Hz	油封代号 空白: NBR V: VITON(高温用) E: EPDM(蒸汽用) Oil Seal Code Blank: NBR V: VITON(for high-temperature) E: EPDM (for steam)

图形符号 | Graphic Symbol



规格 | Specification

型号 Model	2W025-06 2S025-06	2W025-08 2S025-08	2W040-10 2S040-10	2WH012-06 2SH012-06	2WH012-08 2SH012-08	2WH020-10 2SH020-10
工作介质 Working Medium	空气、水、油、瓦斯 Air, Water, Oil, Gas					
动作方式 Motion Pattern	直动式 Direct Drive Type					
型式 Type	常闭型 Normal Close Type			常开型 Normal Open Type		
流量孔径 mm Aperture of Flow Rate	2.5		4.0	1.2		2.0
CV值 CV Value	0.23		0.60	0.05		0.15
接管口径 Joint Pipe Bore	G1/8"	G1/4"	G3/8"	G1/8"	G1/4"	G3/8"
使用流体粘滞度 Operation Fluid Viscosity	20 CST以下 (Below)					
使用压力 Working-pressure	0~0.7MPa			0~2.0MPa		
最大耐压力 Max. Pressure Resistance	1.0MPa			3.5MPa		
工作温度范围 Operating Temperature Range	-5~+80℃					
使用电压范围 Voltage Range	±10%					
本体材质 Material of Body	2W: 黄铜 Brass ; 2S: 不锈钢 Stainless Steel					
油封材质 Material of Oil Seal	NBR, EPDM或VITON / NBR, EPDM or VITON					

*特殊电压及特殊规格请与厂方接洽 Please contact Factory for special voltage and Specification.