ISO9001:2000



Hand-switching Valve







订购码 | Ordering Code









位 通数 24:二位四通 34:三位四通 规格代码 手转阀 Specifica-Position and Way NO. 24:Two-position tion Code Handswitching Four-way 34:Three-position Valve Four-way

形式代号 Ra: 手转阀 Type Code R8:Handswitching

接口口径 底部接口 Joint Pipe Base Joint Bore L6: G1/8" L8: G1/4"

_8

规格 | Specification

1961H 1 electrication					
型 묵	1,11,4400,000	1 11 4400 00	1 11 4400 04	1015 10	KOAD LO
Model	HV400-02	HV400-03	HV400-04	K34R ₈ -L6	K34R ₈ -L8
工作介质 Working Medium	经40 微米过滤的空气 40 Micron Filtered Air				
有效截面积 Effective Sectional Area	30mm²(CV=1.68)			18mm²(CV=1.00)	
接口口径 Joint Pipe Bore	G1/4"	G3/8"	G1/2"	G1/8"	G1/4"
使用压力范围 Working-pressure Range	0~0.8MPa				
使用温度范围 Operating Temperature	0~60℃				

- * 公司可提供密封结构形式为橡胶软密封和陶瓷硬密封的手转阀。
 * Company can offer Hand-switching Valve with soft rubber seals and hard pottery seals as the seal structure form.

外形尺寸 | Overall Dimension

