

手拉阀

Hand-draw Valve



订购码 | Ordering Code

4R

规格代码
4R: 二位五通手拉阀
3R: 二位三通手拉阀
Specification Code
4R: Two-position Five-way Hand-draw Valve
3R: Two-position Three-way Hand-draw Valve

2

系列代号
2: 200 系列
Series Code
2: 200 Series

10

位置数
10: 单头双位置
Motion Pattern
10: Single-head Double-position

-

06

接管口径
06: G1/8"
08: G1/4"

规格 | Specification

型号 Model	4R210-06	4R210-08	3R210-06	3R210-08
工作介质 Working Medium	经 40 微米过滤的空气 40 Micron Filtered Air			
位通数 Position and Way NO.	二位五通 Two-position Five-way		二位三通 Two-position Three-way	
有效截面积 Effective Section Area	14mm ² (CV=0.78)	16mm ² (CV=0.89)	14mm ² (CV=0.78)	16mm ² (CV=0.89)
接口口径 Joint Pipe Bore	进气=出气=排气=G1/8" Air Inlet=Air Outlet=Exhaust=G1/8"	进气=出气=G1/4" 排气=G1/8" Air Inlet=Air Outlet=G1/4" Exhaust=G1/8"	进气=出气=排气=G1/8" Air Inlet=Air Outlet=Exhaust=G1/8"	进气=出气=排气=G1/4" Air Inlet=Air Outlet=Exhaust=G1/4"
使用压力范围 Working-pressure Range	0~0.8MPa			
使用温度范围 Operating Temperature Range	0~60℃			

外形尺寸 | Overall Dimension

